



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S8198** - 9 Watt LED PAR36; 15K Average rated hours; 3000K; Screw Terminal base



### GENERAL

|                         |                                 |
|-------------------------|---------------------------------|
| Company                 | SATCO                           |
| EA Height               | 4.65                            |
| EA Width                | 3.35                            |
| EA Length               | 3.35                            |
| Candle Power            | 1500.0                          |
| Lamp Filament           | LED                             |
| Material                | Glass                           |
| Fixture Type            | Reflector                       |
| Status                  | Active                          |
| Style                   | Utility                         |
| Surge Protection        | Built-in surge protection - 1KV |
| CCT Selectable          | No                              |
| Wattage Selectable      | No                              |
| Finish Family           | Clear                           |
| Additional Info         | Replaces 50W Halogen PAR36      |
| Amps                    | 0.750-0.375A                    |
| Has Camera              | No                              |
| IOT Enabled             | No                              |
| Operating Position      | Universal                       |
| SDS Class               | LED_Lamp                        |
| Indoor Outdoor          | Indoor, Outdoor                 |
| Product Technology      | LED                             |
| Incandescent Equivalent | 40W                             |

### ELECTRICAL

|                     |              |
|---------------------|--------------|
| CCT (Kelvin Temp)   | 3000K        |
| Dimmable            | Non-Dimmable |
| Hours Rated         | 15000        |
| Beam Angle (degree) | 100          |
| Color Temp          | Soft White   |
| CRI                 | 80+          |
| HID Equivalent      | 50W          |
| Lumens              | 800L         |
| Volts               | 12V-24V      |
| Watts               | 9W           |

### PHYSICAL

|               |                |
|---------------|----------------|
| Lamp Base     | Screw Terminal |
| Finish        | Clear          |
| Housing Color | None           |
| ANSI Base     | MP2            |
| Lamp Type     | PAR36          |
| MOD Lamps     | 4.41           |
| MOL           | 2.44           |

### ADDITIONAL INFO

|          |         |
|----------|---------|
| Warranty | 2-Years |
|----------|---------|

### PACKAGING

|                |                |
|----------------|----------------|
| UPC            | 045923081989   |
| Case Cube      | 1.2271         |
| Case Height    | 11.97          |
| Case Length    | 15.35          |
| Case Quantity  | 24             |
| Case UPC       | 10045923081986 |
| Case Weight    | 17.28          |
| Case Width     | 11.54          |
| EA Cube        | 0.0302         |
| EA Height      | 4.65           |
| EA Length      | 3.35           |
| EA Quantity    | 1              |
| EA Weight      | 0.72           |
| EA Width       | 3.35           |
| Inner Cube     | 0.2551         |
| Inner Height   | 5.59           |
| Inner Length   | 10.83          |
| Inner Quantity | 6              |
| Inner UPC      | 20045923081983 |
| Inner Weight   | 5.0            |
| Inner Width    | 7.28           |
| Pack Type      | Box            |
| Web Length     | 2.44           |
| Web Width      | 4.41           |

### COMPLIANCE

|                   |                 |
|-------------------|-----------------|
| FCC Compliant     | Yes             |
| IP Rating         | IP65            |
| Location Rating   | Wet             |
| ROHS Compliant    | Yes             |
| Safety Listing    | Not Applicable  |
| California Ban    | Lawful for sale |
| DLC Approved      | No              |
| Title 20          | Exempt          |
| T24/JA8 Compliant | No              |