



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S8421 - 32 Watt; T8; Fluorescent; 5000K Natural Light; 85 CRI; Medium Bi Pin base



GENERAL

Company	SATCO
EA Height	47.8
EA Width	1.08
EA Length	1.08
Lamp Ballast Type AB	Type A
Ballasting Requirements	For use with Electronic ballasts
Fixture Type	Linear
Hg Content	3.2
Status	Active
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Has Camera	No
IOT Enabled	No
Lens Finish	Gloss White
Lensed	Yes
Mean Lumens	2750
Nominal Length	48.0
Operating Position	Universal
SDS Class	Linear_Fluorescent_Lamp
Product Technology	Fluorescent
Start Method	Instant Start

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Hours Rated	24000
Beam Angle (degree)	360
Color Temp	Natural Light
CRI	85+
Operating Temp	Ballast Dependent
Lumens	2900L
Watts	32W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	Gloss White
Housing Color	None
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	47.78

ADDITIONAL INFO

Warranty	3-Years
----------	---------

PACKAGING

UPC	045923084218
Case Cube	1.2367
Case Height	6.1
Case Length	49.41
Case Quantity	30
Case UPC	10045923084215
Case Weight	13.46
Case Width	7.09
EA Cube	0.0323
EA Height	47.8
EA Length	1.08
EA Quantity	1
EA Weight	0.42
EA Width	1.08
Pack Type	Sleeve
Web Length	47.78
Web Width	1.0

COMPLIANCE

CA Prop 65	Lead
ROHS Compliant	Yes
Safety Listing	Not Applicable
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24/JA8 Compliant	No
US State Ban	CA, CO, HI, ME, MN, OR, RI, VT