



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S8436** - 32 Watt; T8; Fluorescent; 6500K Daylight; 82 CRI; Medium Bi Pin base



### GENERAL

Company	SATCO
EA Height	47.8
EA Width	1.08
EA Length	1.08
Lamp Ballast Type AB	Type A
Ballasting Requirements	For use with Electronic ballasts
Fixture Type	Linear
Hg Content	3.2
Status	Active
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Has Camera	No
IOT Enabled	No
Lens Finish	Gloss White
Lensed	Yes
Mean Lumens	2700
Nominal Length	48.0
Operating Position	Universal
SDS Class	Linear_Fluorescent_Lamp
Product Technology	Fluorescent

### ELECTRICAL

CCT (Kelvin Temp)	6500K
Dimmable	Non-Dimmable
Hours Rated	24000
Beam Angle (degree)	360
Color Temp	Daylight
CRI	80+
Operating Temp	Ballast Dependent
Lumens	2850L
Watts	32W

### PHYSICAL

Lamp Base	Medium Bi Pin
Finish	Gloss White
Housing Color	None
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	47.78

### ADDITIONAL INFO

Warranty	3-Years
----------	---------

### PACKAGING

UPC	045923084362
Case Cube	1.2367
Case Height	6.1
Case Length	49.41
Case Quantity	30
Case UPC	10045923084369
Case Weight	13.46
Case Width	7.09
EA Cube	0.0323
EA Height	47.8
EA Length	1.08
EA Quantity	1
EA Weight	0.42
EA Width	1.08
Pack Type	Sleeve
Web Length	47.78
Web Width	1.0

### COMPLIANCE

CA Prop 65	Lead
ROHS Compliant	Yes
Safety Listing	Not Applicable
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24/JA8 Compliant	No
US State Ban	CA, CO, HI, ME, MN, OR, RI, VT