



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S8438** - 25 Watt; T8; Fluorescent; 3000K Warm White; 85 CRI; Medium Bi Pin base



**GENERAL**

|                         |                                  |
|-------------------------|----------------------------------|
| Company                 | SATCO                            |
| EA Height               | 1.08                             |
| EA Width                | 1.08                             |
| EA Length               | 47.8                             |
| Lamp Ballast Type AB    | Type A                           |
| Ballasting Requirements | For use with Electronic ballasts |
| Fixture Type            | Linear                           |
| Hg Content              | 3.5                              |
| Status                  | Active                           |
| CCT Selectable          | No                               |
| Wattage Selectable      | No                               |
| Finish Family           | White                            |
| Has Camera              | No                               |
| IOT Enabled             | No                               |
| Lens Finish             | Gloss White                      |
| Lensed                  | Yes                              |
| Mean Lumens             | 2280                             |
| Nominal Length          | 48.0                             |
| Operating Position      | Universal                        |
| SDS Class               | Linear_Fluorescent_Lamp          |
| Product Technology      | Fluorescent                      |
| Start Method            | Instant Start                    |

**ELECTRICAL**

|                     |                   |
|---------------------|-------------------|
| CCT (Kelvin Temp)   | 3000K             |
| Dimmable            | Non-Dimmable      |
| Hours Rated         | 30000             |
| Beam Angle (degree) | 360               |
| Color Temp          | Warm White        |
| CRI                 | 85+               |
| Operating Temp      | Ballast Dependent |
| Lumens              | 2400L             |
| Watts               | 25W               |

**PHYSICAL**

|               |               |
|---------------|---------------|
| Lamp Base     | Medium Bi Pin |
| Finish        | Gloss White   |
| Housing Color | None          |
| ANSI Base     | G13           |
| Lamp Type     | T8            |
| MOD Lamps     | 1.0           |
| MOL           | 47.78         |

**ADDITIONAL INFO**

|          |         |
|----------|---------|
| Warranty | 3-Years |
|----------|---------|

**PACKAGING**

|               |                |
|---------------|----------------|
| UPC           | 045923084386   |
| Case Cube     | 1.2367         |
| Case Height   | 6.1            |
| Case Length   | 49.41          |
| Case Quantity | 30             |
| Case UPC      | 10045923084383 |
| Case Weight   | 13.46          |
| Case Width    | 7.09           |
| EA Cube       | 0.0323         |
| EA Height     | 1.08           |
| EA Length     | 47.8           |
| EA Quantity   | 1              |
| EA Weight     | 0.42           |
| EA Width      | 1.08           |
| Pack Type     | Sleeve         |
| Web Length    | 47.78          |
| Web Width     | 1.0            |

**COMPLIANCE**

|                |                                |
|----------------|--------------------------------|
| CA Prop 65     | Lead                           |
| ROHS Compliant | Yes                            |
| Safety Listing | Not Applicable                 |
| California Ban | Non-Compliant                  |
| DLC Approved   | No                             |
| Title 20       | No                             |
| T24 Compliant  | No                             |
| US State Ban   | CA, CO, HI, ME, MN, OR, RI, VT |