



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S8458 - 32 Watt; T8; U-Bend Fluorescent; 4100K Cool White; 82 CRI; Medium Bi Pin base



GENERAL

Company	SATCO
EA Height	7.16
EA Width	23.03
EA Length	1.1
Lamp Ballast Type AB	Type A
Ballasting Requirements	For use with Electronic ballasts
Fixture Type	U-Bend
Hg Content	7.5
Status	Active
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Has Camera	No
IOT Enabled	No
Leg Spacing	6.0
Lens Finish	White
Lensed	Yes
Mean Lumens	2700
Nominal Length	22.5
Operating Position	Universal
SDS Class	Linear_Fluorescent_Lamp
Product Technology	Fluorescent
Start Method	Instant Start

ELECTRICAL

CCT (Kelvin Temp)	4100K
Dimmable	Non-Dimmable
Hours Rated	20000
Beam Angle (degree)	360
Color Temp	Cool White
CRI	80+
Operating Temp	Ballast Dependent
Lumens	3000L
Watts	32W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	WHITE
Housing Color	None
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	22.0

ADDITIONAL INFO

Warranty	3-Years
----------	---------

PACKAGING

UPC	045923084584
Case Cube	2.094
Case Height	10.24
Case Length	23.62
Case Quantity	16
Case UPC	10045923084581
Case Weight	15.18
Case Width	14.96
EA Cube	0.105
EA Height	7.16
EA Length	1.1
EA Quantity	1
EA Weight	0.85
EA Width	23.03
Pack Type	Box
Web Length	22.0
Web Width	1.0

COMPLIANCE

ROHS Compliant	Yes
Safety Listing	Not Applicable
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24/JA8 Compliant	No
US State Ban	CA, CO, HI, ME, MN, OR, RI, VT