



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S8537 - 9 Watt LED PL 2-Pin; 3500K; 950 Lumens; G24d base; 50000 Average rated hours; 120 Deg. Beam Angle; Vertical; Type B; Ballast Bypass



GENERAL

Company	SATCO
EA Height	4.84
EA Width	1.93
EA Length	1.93
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Lamp Filament	LED
Fixture Type	PL
Status	Active
Style	Transitional
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.075-0.032A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Operating Position	Base Up or Down
Power Factor	0.99
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	18W/26W
Incandescent Equivalent	40W

ELECTRICAL

CCT (Kelvin Temp)	3500K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	Neutral White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	950L
Volts	120V-277V
Watts	9W

PHYSICAL

Lamp Base	G24d (2-Pin)
Finish	Frost
Housing Color	White
ANSI Base	G24d
Lamp Type	PL
MOD Lamps	1.91
MOL	4.69

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	2-pin LED lamps work in both 2-pin (magnetic) and 4-pin (electronic) sockets.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923085376
Case Cube	0.7153
Case Height	11.0
Case Length	10.6
Case Quantity	50
Case UPC	10045923085373
Case Weight	15.67
Case Width	10.6
EA Cube	0.0104
EA Height	4.84
EA Length	1.93
EA Quantity	1
EA Weight	0.31
EA Width	1.93
Inner Cube	0.1236
Inner Height	10.0
Inner Length	4.17
Inner Quantity	10
Inner UPC	20045923085370
Inner Weight	0.0
Inner Width	5.12
Pack Type	Box
Web Length	4.69
Web Width	1.91

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No