



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S8746 - 8 Watt LED PL GU24 base; 3000K; Type B; Ballast Bypass; 920 Lumens; 50000 Average rated hours; 120 deg. Beam Angle; 120-277 Volt



GENERAL

Company	SATCO
EA Height	7.28
EA Width	1.65
EA Length	1.65
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Fixture Type	PL
Status	Obsolete
Style	Transitional
Surge Protection	Built-in-surge protection - 0.5KV
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.067-0.029A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Operating Position	Universal
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	13W/18W
Incandescent Equivalent	40W

ELECTRICAL

CCT (Kelvin Temp)	3000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	Warm White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	920L
Volts	120V-277V
Watts	8W

PHYSICAL

Lamp Base	Bi Pin GU24
Finish	Frost
Housing Color	White
ANSI Base	GU24
Lamp Type	PL
MOD Lamps	1.38
MOL	6.41

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923087462
Case Cube	0.9555
Case Height	9.1
Case Length	18.9
Case Quantity	50
Case UPC	10045923087469
Case Weight	15.9
Case Width	9.6
EA Cube	0.0115
EA Height	7.28
EA Length	1.65
EA Quantity	1
EA Weight	0.3
EA Width	1.65
Inner Cube	0.1419
Inner Height	7.7
Inner Length	9.1
Inner Quantity	10
Inner UPC	20045923087466
Inner Weight	3.0
Inner Width	3.5
Pack Type	Box
Web Length	6.41
Web Width	1.38

COMPLIANCE

FCC Compliant	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Listed
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24 Compliant	No
US State Ban	CA