



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S8750 - 8 Watt LED PL; GU24 Base; 27K/30K/35K/40K/50K CCT Selectable; Type B Ballast Bypass; 120-277 Volt



GENERAL

| | |
|---------------------------|-----------------------------------|
| Company | SATCO |
| EA Height | 7.28 |
| EA Width | 1.65 |
| EA Length | 1.65 |
| Lamp Ballast Type AB | Type B |
| Ballasting Requirements | Ballast Bypass |
| Candle Power | 200.0 |
| Lamp Filament | LED |
| Material | Plastic |
| Fixture Type | Miniature |
| Status | Active |
| Style | Transitional |
| Surge Protection | Built-in-surge protection - 0.5KV |
| Total Harmonic Distortion | <20% |
| CCT Selectable | Yes |
| Wattage Selectable | No |
| Finish Family | White |
| Amps | 0.070A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Frost |
| Operating Position | Universal |
| Power Factor | 0.9 |
| SDS Class | LED_Lamp |
| Indoor Outdoor | Indoor |
| Product Technology | LED |
| Fluor Equiv | 18W |
| Incandescent Equivalent | 60W |

ELECTRICAL

| | |
|---------------------|-------------------------------|
| CCT (Kelvin Temp) | 2700K/3000K/3500K/4000K/5000K |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 120 |
| Color Temp | Warm White to Natural Light |
| CRI | 80+ |
| Operating Frequency | 50/60Hz |
| Operating Temp | -4F to +113F (-20C to +45C) |
| Lumens | 950L/975L/1000L/1050L/1050L |
| Volts | 120V-277V |
| Watts | 8W |

PHYSICAL

| | |
|---------------|-------------|
| Lamp Base | Bi Pin GU24 |
| Finish | Frost |
| Housing Color | White |
| ANSI Base | GU24 |
| Lamp Type | PL |
| MOD Lamps | 1.38 |
| MOL | 6.5 |

ADDITIONAL INFO

| | |
|----------------------------|---------|
| Warranty | 5-Years |
| Rated For Enclosed Fixture | Yes |

PACKAGING

| | |
|----------------|----------------|
| UPC | 045923087509 |
| Case Cube | 0.9563 |
| Case Height | 9.06 |
| Case Length | 18.9 |
| Case Quantity | 50 |
| Case UPC | 10045923087506 |
| Case Weight | 14.33 |
| Case Width | 9.65 |
| EA Cube | 0.0115 |
| EA Height | 7.28 |
| EA Length | 1.65 |
| EA Quantity | 1 |
| EA Weight | 0.3 |
| EA Width | 1.65 |
| Inner Cube | 0.1461 |
| Inner Height | 7.87 |
| Inner Length | 9.06 |
| Inner Quantity | 10 |
| Inner UPC | 20045923087503 |
| Inner Weight | 0.3 |
| Inner Width | 3.54 |
| Pack Type | Box |
| Web Length | 6.5 |
| Web Width | 1.38 |

COMPLIANCE

| | |
|-------------------|-----------------------------------|
| FCC Compliant | Yes |
| Location Rating | Damp |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Certified, cULus - Listed |
| California Ban | Non-Compliant |
| DLC Approved | No |
| Title 20 | No |
| T24/JA8 Compliant | No |
| US State Ban | CA |