



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S8760** - 8 Watt LED PL; E26 Base; 27K/30K/35K/40K/50K CCT Selectable; Type B Ballast Bypass; 120-277 Volt



**GENERAL**

Company	SATCO
EA Height	7.28
EA Width	1.65
EA Length	1.65
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Candle Power	200.0
Lamp Filament	LED
Material	Plastic
Fixture Type	Miniature
Status	Active
Style	Transitional
Surge Protection	Built-in-surge protection - 0.5KV
Total Harmonic Distortion	<20%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.070A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	18W
Incandescent Equivalent	60W

**ELECTRICAL**

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K/5000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	Warm White to Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	950L/975L/1000L/1050L/1050L
Volts	120V-277V
Watts	8W

**PHYSICAL**

Lamp Base	Medium
Finish	Frost
Housing Color	White
ANSI Base	E26
Lamp Type	PL
MOD Lamps	1.38
MOL	6.5

**ADDITIONAL INFO**

Warranty	5-Years
Rated For Enclosed Fixture	Yes

**PACKAGING**

UPC	045923087608
Case Cube	0.9563
Case Height	9.06
Case Length	18.9
Case Quantity	50
Case UPC	10045923087605
Case Weight	14.33
Case Width	9.65
EA Cube	0.0115
EA Height	7.28
EA Length	1.65
EA Quantity	1
EA Weight	0.3
EA Width	1.65
Inner Cube	0.1461
Inner Height	7.87
Inner Length	9.06
Inner Quantity	10
Inner UPC	20045923087602
Inner Weight	0.3
Inner Width	3.54
Pack Type	Box
Web Length	6.5
Web Width	1.38

**COMPLIANCE**

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24 Compliant	No
US State Ban	CA