Project / Job Name:

Location:

Fixture Type:

Notes:



S9294 - 12 Watt T8 U-Bend LED; 50000 Average rated hours; Medium bi-pin base; 1800 Lumens; 3000K

GENERAL

Generational SKU	S18413
Company	SATCO
EA Height	1.3
EA Width	7.5
EA Length	23.2
Lamp Ballast Type AB	Type A
Ballasting Requirements	May not be compatible with all rapid start ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required
Lamp Filament	LED
Fixture Type	U-Bend
Status	Discontinued
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Has Camera	No
IOT Enabled	No
Leg Spacing	6.0
Lens Finish	Gloss White
Lensed	Yes
Nominal Length	22.5
Operating Position	Universal
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	32W
Incandescent Equivalent	60W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	3000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	230
Color Temp	Warm White
CRI	80+
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1800L
Volts	Ballast Dependent
Watts	12W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	Gloss White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	22.5

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.

PACKAGING

UPC	045923092947
Case Cube	2.0847
Case Height	9.5
Case Length	24.0
Case Quantity	12
Case UPC	10045923092944
Case Weight	10.8
Case Width	15.8
EA Cube	0.1309
EA Height	1.3
EA Length	23.2
EA Quantity	1
EA Weight	0.7
EA Width	7.5
Pack Type	Box
Web Length	22.5
Web Width	1.0

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026