



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9380 - 4.5 Watt; LED MR16; 3000K; 40 deg. Beam Angle; GU10 base; 120 Volt



GENERAL

Company	SATCO
EA Height	2.8
EA Width	1.97
EA Length	1.97
Candle Power	510.0
Center Beam Candle Power	510
Lamp Filament	LED
Fixture Type	MR
Spot Type	FL - Flood
Status	Active
Style	Contemporary
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.038A
Has Camera	No
IOT Enabled	No
Lens Finish	Array White
Lensed	Yes
Operating Position	Universal
Power Factor	0.91
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	35W

ELECTRICAL

CCT (Kelvin Temp)	3000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	40
Color Temp	Warm White
CRI	80+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-13F to +113F (-25C to +45C)
Lumens	360L
Volts	120v
Watts	4.5W

PHYSICAL

Lamp Base	Bi Pin GU10
Finish	WHITE
Housing Color	White
ANSI Base	GU10
Lamp Type	MR16
MOD Lamps	1.969
MOL	2.165

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923093807
Case Cube	0.5312
Case Height	7.09
Case Length	13.7
Case Quantity	48
Case UPC	10045923093804
Case Weight	7.67
Case Width	9.45
EA Cube	0.0063
EA Height	2.8
EA Length	1.97
EA Quantity	1
EA Weight	0.14
EA Width	1.97
Inner Cube	0.0968
Inner Height	6.02
Inner Length	6.42
Inner Quantity	12
Inner UPC	20045923093801
Inner Weight	1.81
Inner Width	4.33
Pack Type	Box
Web Length	2.165
Web Width	1.969

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Yes
T24/JA8 Compliant	No