



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9388 - 6.5 Watt PAR16 LED; 3000K; 40 deg. Beam Angle; Medium base; 120 Volt



GENERAL

Company	SATCO
EA Height	3.54
EA Width	2.05
EA Length	2.05
Candle Power	700.0
Center Beam Candle Power	700
Lamp Filament	LED
Fixture Type	PAR
Status	Active
Style	Utility
CCT Selectable	No
Wattage Selectable	No
Finish Family	Clear
Amps	0.054A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lensed	Yes
Operating Position	Universal
Power Factor	0.92
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	60W

ELECTRICAL

CCT (Kelvin Temp)	3000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	40
Color Temp	Warm White
CRI	80+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-13F to +113F (-25C to +45C)
Lumens	500L
Volts	120v
Watts	6.5W

PHYSICAL

Lamp Base	Medium
Finish	Clear
Housing Color	White
ANSI Base	E26
Lamp Type	PAR16
MOD Lamps	2.0
MOL	2.88

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923093883
Case Cube	0.6771
Case Height	8.46
Case Length	14.17
Case Quantity	48
Case UPC	10045923093880
Case Weight	8.51
Case Width	9.76
EA Cube	0.0086
EA Height	3.54
EA Length	2.05
EA Quantity	1
EA Weight	0.15
EA Width	2.05
Inner Cube	0.1318
Inner Height	7.5
Inner Length	6.75
Inner Quantity	12
Inner UPC	20045923093887
Inner Weight	1.84
Inner Width	4.5
Pack Type	Box
Web Length	2.88
Web Width	2.0

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Yes
T24/JA8 Compliant	No