



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9415 - 13 Watt PAR30 Short Neck LED; 2700K; 40 deg. Beam Angle; Medium base; 120 Volt



GENERAL

Company	SATCO
EA Height	4.14
EA Width	3.94
EA Length	3.94
Center Beam Candle Power	850
Dimmable Text	Forward Phase or Reverse Phase or Phase Selectable
Lamp Filament	LED
Fixture Type	PAR
Status	Discontinued
CCT Selectable	No
Wattage Selectable	No
Finish Family	No Finish
Amps	0.108A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lensed	Yes
Operating Position	Universal
Power Factor	1
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Incandescent Equivalent	50W

ELECTRICAL

CCT (Kelvin Temp)	2700K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	40
Color Temp	Warm White
CRI	80+
Dimming Type	120V only, Phase cut
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	1000L
Volts	120v
Watts	13W

PHYSICAL

Lamp Base	Medium
Finish	Clear
Housing Color	Silver
ANSI Base	E26
Lamp Type	PAR30SN
MOD Lamps	3.75
MOL	3.63

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923094156
Case Cube	0.694
Case Height	5.32
Case Length	17.34
Case Quantity	12
Case UPC	10045923094153
Case Weight	6.25
Case Width	13.0
EA Cube	0.0372
EA Height	4.14
EA Length	3.94
EA Quantity	1
EA Weight	0.29
EA Width	3.94
Inner Cube	0.269
Inner Height	4.53
Inner Length	12.41
Inner Quantity	6
Inner UPC	20045923094150
Inner Weight	4.2
Inner Width	8.27
Pack Type	Box
Web Length	3.63
Web Width	3.75

COMPLIANCE

CA T20 Compliant Substitute	S9486
FCC Compliant	Yes
IP Rating	IP65
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cULus
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24 Compliant	No
US State Ban	CA