



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9624 - 9.5 Watt; BR30 LED; 105 deg. Beam Angle; 2700K; GU24 base; 120 Volt; Dimmable



GENERAL

Company	SATCO
EA Height	5.51
EA Width	3.86
EA Length	3.86
Candle Power	260.0
Center Beam Candle Power	260
Dimmable Text	Forward Phase or Reverse Phase or Phase Selectable
Lamp Filament	LED
Fixture Type	Reflector
Status	Active
Style	Contemporary
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Can be used as the LED replacement for S8224
Amps	0.079A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Operating Position	Universal
Power Factor	0.91
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	65W

ELECTRICAL

CCT (Kelvin Temp)	2700K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	105
Color Temp	Warm White
CRI	80+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-25C (-13F) to +45C (+113F)
Lumens	750L
Volts	120v
Watts	9.5W

PHYSICAL

Lamp Base	Bi Pin GU24
Finish	Frost
Housing Color	Gray
ANSI Base	GU24
Lamp Type	BR30
MOD Lamps	3.74
MOL	4.961

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	No

PACKAGING

UPC	045923096242
Case Cube	0.8839
Case Height	7.01
Case Length	17.13
Case Quantity	12
Case UPC	10045923096249
Case Weight	5.51
Case Width	12.72
EA Cube	0.0475
EA Height	5.51
EA Length	3.86
EA Quantity	1
EA Weight	0.36
EA Width	3.86
Inner Cube	0.3365
Inner Height	5.91
Inner Length	12.13
Inner Quantity	6
Inner UPC	20045923096246
Inner Weight	2.49
Inner Width	8.11
Pack Type	Box
Web Length	4.961
Web Width	3.74

COMPLIANCE

CA T20 Compliant Substitute	S29626
FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24 Compliant	No
US State Ban	CA