



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S9626** - 9.5 Watt; BR30 LED; 105 deg. Beam Angle; 2700K; GU24 base; 120 Volt; 90 CRI; Dimmable



**GENERAL**

Company	SATCO
EA Height	5.51
EA Width	3.86
EA Length	3.86
Candle Power	220.0
Dimmable Text	Forward Phase or Reverse Phase or Phase Selectable
Lamp Filament	LED
Fixture Type	Reflector
Status	Obsolete
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.079A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	65W

**ELECTRICAL**

CCT (Kelvin Temp)	2700K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	105
Color Temp	Warm White
CRI	90+
Dimming Type	Forward Phase or Reverse Phase or Phase Selectable
Operating Temp	-25C (-13F) to +45C (+113F)
Lumens	650L
Volts	120v
Watts	9.5W

**PHYSICAL**

Lamp Base	Bi Pin GU24
Finish	Frost
Housing Color	Gray
ANSI Base	GU24
Lamp Type	BR30
MOD Lamps	3.75
MOL	4.94

**ADDITIONAL INFO**

Warranty	5-Years
Rated For Enclosed Fixture	No

**PACKAGING**

UPC	045923096266
Case Cube	0.8839
Case Height	7.01
Case Length	17.13
Case Quantity	12
Case UPC	10045923096263
Case Weight	5.51
Case Width	12.72
EA Cube	0.0475
EA Height	5.51
EA Length	3.86
EA Quantity	1
EA Weight	0.36
EA Width	3.86
Inner Cube	0.3365
Inner Height	5.91
Inner Length	12.13
Inner Quantity	6
Inner UPC	20045923096260
Inner Weight	2.49
Inner Width	8.11
Pack Type	Box
Web Length	4.94
Web Width	3.75

**COMPLIANCE**

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	California T24 Listed
DLC Approved	No
Title 20	Yes
T24 Compliant	Yes