



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9632 - 6.5 Watt; LED R20; 4000K; 107 deg. Beam Angle; Medium base; 120 Volt; Dimmable



GENERAL

Company	SATCO
EA Height	4.25
EA Width	2.6
EA Length	2.6
Candle Power	180.0
Center Beam Candle Power	180
Lamp Filament	LED
Fixture Type	Reflector
Status	Active
Style	Contemporary
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.054A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Operating Position	Universal
Power Factor	0.92
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	45W

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	107
Color Temp	Cool White
CRI	80+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-13F to +113F (-25C to +45C)
Lumens	525L
Volts	120v
Watts	6.5W

PHYSICAL

Lamp Base	Medium
Finish	Frost
Housing Color	Gray
ANSI Base	E26
Lamp Type	R20
MOD Lamps	2.5
MOL	3.94

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923096327
Case Cube	0.6531
Case Height	10.43
Case Length	12.05
Case Quantity	24
Case UPC	10045923096324
Case Weight	5.6
Case Width	8.98
EA Cube	0.0166
EA Height	4.25
EA Length	2.6
EA Quantity	1
EA Weight	0.19
EA Width	2.6
Inner Cube	0.125
Inner Height	4.65
Inner Length	8.31
Inner Quantity	6
Inner UPC	20045923096321
Inner Weight	1.28
Inner Width	5.59
Pack Type	Box
Web Length	3.94
Web Width	2.5

COMPLIANCE

CA T20 Compliant Substitute	S28491
FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24/JA8 Compliant	No
US State Ban	CA