



Project / Job Name:

Location:

Fixture Type:

Notes:

S9710 - 25 Watt T5 LED; Miniature bi-pin base; 4000K; 50000 Average rated hours; 3200 Lumens



GENERAL

Company	SATCO
EA Height	0.71
EA Width	0.71
EA Length	46.2
Ballasting Requirements	May not be compatible with all instant start ballasts; Ballast required; Direct Replacement-for use on Electronic Instant Start ballasts with no rewiring required
Lamp Filament	LED
Fixture Type	Linear
Status	Obsolete
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	High efficacy
IOT Enabled	No
Lens Finish	Gloss White
Lensed	Yes
Nominal Length	48.0
Operating Position	Universal
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	54W
Incandescent Equivalent	100W

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	185
Color Temp	Cool White
CRI	80+
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	3200L
Watts	25W

PHYSICAL

Lamp Base	Miniature Bi Pin
Finish	Gloss White
ANSI Base	G5
Lamp Type	T5
MOD Lamps	0.63
MOL	48.0

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.

PACKAGING

UPC	045923097102
Case Cube	0.5787
Case Height	3.3
Case Length	48.1
Case Quantity	10
Case UPC	10045923097109
Case Weight	4.41
Case Width	6.3
EA Cube	0.0135
EA Height	0.71
EA Length	46.2
EA Quantity	1
EA Weight	0.31
EA Width	0.71
Pack Type	Egg Crate
Web Length	48.0
Web Width	0.63

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No