



**S9720** - 15 Watt T8 LED; Medium bi-pin base; 3000K; 50000 Average rated hours; 1800 Lumens; Type B; Ballast Bypass; Single Ended Wiring


**GENERAL**

Company	SATCO
EA Height	1.18
EA Width	1.18
EA Length	48.43
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Status	Obsolete
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.125-0.054A
Has Camera	No
IOT Enabled	No
Lens Finish	Gloss White
Lens Material	Glass
Lensed	Yes
Nominal Length	48.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	25W-32W
Incandescent Equivalent	100W

**PACKAGING**

UPC	045923097201
Case Cube	1.0244
Case Height	4.3
Case Length	49.6
Case Quantity	10
Case UPC	10045923097208
Case Weight	6.4
Case Width	8.3
EA Cube	0.039
EA Height	1.18
EA Length	48.43
EA Quantity	1
EA Weight	0.6
EA Width	1.18
Pack Type	Egg Crate
Web Length	48.0
Web Width	1.0

**COMPLIANCE**

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No

**ELECTRICAL**

CCT (Kelvin Temp)	3000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	230
Color Temp	Warm White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	1800L
Volts	120V-277V
Watts	15W

**PHYSICAL**

Lamp Base	Medium Bi Pin
Finish	Gloss White
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	48.0

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes