



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S9729** - 7.5 watt LED Downlight Retrofit; 4'' Baffle; 3000K; GU5.3 socket for MR16 retrofit; 12 volts



### GENERAL

Company	SATCO
EA Height	5.91
EA Width	3.62
EA Length	5.51
Bulb Included	Integrated
Diameter	5.31
Material	Aluminum
Fixture Type	Downlight Retrofit
Includes	Bi Pin GU5.3 Adapter included with this fixture
Status	Discontinued
Style	Modern and Contemporary
CCT Selectable	No
Wattage Selectable	No
Can Size	4 in.
Finish Family	White
Additional Info	The dimming control will depend on the Driver or transformer that is been used, as an example if a magnetic Tramformer is being used it will require an LV dimmer (for example Lutron DVLV-600P-WH) if an Electronic transformer is being used it will require an ELV dimmer (Lutron DVELV-300P-WH).
Amps	0.625A
Has Camera	No
IOT Enabled	No
SDS Class	LED Fixture
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	50W

### PACKAGING

UPC	045923097294
Case Cube	1.0302
Case Height	6.69
Case Length	22.84
Case Quantity	12
Case UPC	10045923097291
Case Weight	7.34
Case Width	11.65
EA Cube	0.0682
EA Height	5.91
EA Length	5.51
EA Quantity	1
EA Weight	0.51
EA Width	3.62
Pack Type	Box
Web Height	2.91
Web Width	5.31

### COMPLIANCE

CA Prop 65	Lead
FCC Compliant	Yes
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	Not Applicable
California Ban	Lawful for sale
DLC Approved	No
Energy Star Certified	No
Title 20	Exempt
T24 Compliant	No

### ELECTRICAL

CCT (Kelvin Temp)	3000K
Dimmable	Yes-Dimmable
Hours Rated	35000
Beam Angle (degree)	90
Color Temp	Warm White
CRI	90+
Dimming Type	Low Voltage, Phase cut
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	460L
Volts	12V
Watts	7.5W

### PHYSICAL

Lamp Base	Bi Pin GU5.3
Finish	White / Frosted
ANSI Base	GU5.3 Adapter
Lamp Type	Integrated LED
Fixture Shape	Round

### ADDITIONAL INFO

Warranty	3-Years
Installation Notes	GU5.3 base