SATCO | NUVO



Project / Job Name:

Location:

Fixture Type:

Notes:

S9730 - 23 Watt PLL LED direct replacement; 2G11 base; 2600 Lumens; Ballast Dependent

GENERAL

Company	SATCO
EA Height	1.1
EA Width	1.81
EA Length	22.91
Lamp Ballast Type AB	Type A
Ballasting Requirements	May not be compatible with all rapid start ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required
Lamp Filament	LED
Fixture Type	PL
Status	Obsolete
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.192-0.083A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Operating Position	Universal
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	40W
Incandescent Equivalent	100W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	3500K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	360
Color Temp	Neutral White
CRI	80+
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	2600L
Volts	Ballast Dependent
Watts	23W

PHYSICAL

Lamp Base	4-Pin
Finish	Frost
Housing Color	White
ANSI Base	2G11
Lamp Type	T5
MOD Lamps	1.75
MOL	22.5

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.

PACKAGING

UPC	045923097300
Case Cube	0.3847
Case Height	4.33
Case Length	23.62
Case Quantity	10
Case UPC	10045923097307
Case Weight	4.18
Case Width	6.5
EA Cube	0.0264
EA Height	1.1
EA Length	22.91
EA Quantity	1
EA Weight	0.53
EA Width	1.81
Pack Type	Box
Web Length	22.5
Web Width	1.75

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026