

**S9734** - 14 Watt T8 LED; Medium bi-pin base; 3000K;  
50000 Average rated hours; 1800 Lumens


**GENERAL**

Company	SATCO
EA Height	1.18
EA Width	1.18
EA Length	48.43
Ballasting Requirements	May not be compatible with all rapid start, dimmable, and emergency ballasts; Ballast required; Approved for enclosed fixtures when used only on low or normal ballast factor systems
Lamp Filament	LED
Fixture Type	Linear
Product Notes	25watt - 32watt Fluorescent equivalency
Status	Obsolete
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Has Camera	No
IOT Enabled	No
Lens Finish	Gloss White
Lensed	Yes
Nominal Length	48.0
Operating Position	Universal
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	25W-32W
Incandescent Equivalent	100W

**PACKAGING**

UPC	045923097348
Case Cube	1.0316
Case Height	4.33
Case Length	49.6
Case Quantity	10
Case UPC	10045923097345
Case Weight	6.4
Case Width	8.3
EA Cube	0.039
EA Height	1.18
EA Length	48.43
EA Quantity	1
EA Weight	1.98
EA Width	1.18
Pack Type	Egg Crate
Web Length	48.0
Web Width	1.0

**COMPLIANCE**

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No

**ELECTRICAL**

CCT (Kelvin Temp)	3000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	230
Color Temp	Warm White
CRI	80+
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	1800L
Watts	14W

**PHYSICAL**

Lamp Base	Medium Bi Pin
Finish	Gloss White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	48.0

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.