



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9750 - 30 Watt - LED HID Replacement; 5000K; Medium base; Adjustable beam angle; 100-277 Volt



GENERAL

Company	SATCO
EA Height	7.8
EA Width	4.7
EA Length	4.7
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Fixture Type	Corncob
Status	Obsolete
CCT Selectable	No
Wattage Selectable	No
Finish Family	No Finish
Additional Info	Width 360 deg 3.2 in.; Width 270 deg 6.8 in.; Width 180 deg 7.7 in.
Amps	0.300-0.108A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lensed	Yes
Minimum Compartment Size	Length: 11 in. Width: 8 in. Depth: 8 in.
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	55W
Incandescent Equivalent	200W

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	360
Color Temp	Natural Light
CRI	80+
Operating Temp	-20C (-4F) to +65C (+149F)
HID Equivalent	150W
Lumens	3900L
Volts	120V-277V
Watts	30W

PHYSICAL

Lamp Base	Medium
Finish	Clear
Housing Color	White
ANSI Base	E26
Lamp Type	Corncob
MOD Lamps	3.19
MOL	6.38

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures. Arms fully open diameter is 7.69 inches
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923097508
Case Cube	2.5613
Case Height	13.58
Case Length	18.31
Case Quantity	24
Case UPC	10045923097505
Case Weight	42.55
Case Width	17.8
EA Cube	0.0997
EA Height	7.8
EA Length	4.7
EA Quantity	1
EA Weight	1.62
EA Width	4.7
Inner Cube	0.5222
Inner Height	8.66
Inner Length	12.6
Inner Quantity	6
Inner UPC	20045923097502
Inner Weight	10.09
Inner Width	8.27
Pack Type	Box
Web Length	6.38
Web Width	3.19

COMPLIANCE

FCC Compliant	Yes
IP Rating	IP65
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No