



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9752 - 60 Watt - LED HID Replacement; 5000K; Mogul extended base; Adjustable beam angle; 100-277 Volt



GENERAL

Company	SATCO
EA Height	10.2
EA Width	5.9
EA Length	5.9
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Fixture Type	Corncob
Status	Obsolete
Working Voltage	AC 90-305V
CCT Selectable	No
Wattage Selectable	No
Finish Family	No Finish
Additional Info	Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in.
Amps	0.600-0.217A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lensed	Yes
Minimum Compartment Size	Length: 8.27 in. Width: 9.25 in. Depth: 9.25 in.
Operating Position	Universal
Power Factor	>.9
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	85W
Incandescent Equivalent	500W

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	360
Color Temp	Natural Light
CRI	80+
Operating Frequency	50-60Hz
Operating Temp	-20C (-4F) to +65C (+149F)
HID Equivalent	250W
Lumens	7800L
Volts	120V-277V
Watts	60W

PHYSICAL

Lamp Base	Mogul Extended
Finish	Clear
Housing Color	White
ANSI Base	EX39
Lamp Type	Corncob
MOD Lamps	3.81
MOL	8.56

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures. Arms fully open diameter is 9.31 inches
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923097522
Case Cube	2.0906
Case Height	10.43
Case Length	21.46
Case Quantity	12
Case UPC	10045923097529
Case Weight	34.45
Case Width	16.14
EA Cube	0.2055
EA Height	10.2
EA Length	5.9
EA Quantity	1
EA Weight	2.66
EA Width	5.9
Inner Cube	0.8596
Inner Height	10.24
Inner Length	15.35
Inner Quantity	6
Inner UPC	20045923097526
Inner Weight	16.38
Inner Width	9.45
Pack Type	Box
Web Length	8.56
Web Width	3.81

COMPLIANCE

FCC Compliant	Yes
IP Rating	IP65
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No