



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S9761** - 18 Watt; LED PAR38; 4000K; 25 deg. Beam Angle; Medium base; 100-277 Volt



### GENERAL

Company	SATCO
EA Height	6.1
EA Width	5.71
EA Length	5.71
Center Beam Candle Power	4660
Lamp Filament	LED
Fixture Type	PAR
Status	Discontinued
CCT Selectable	No
Wattage Selectable	No
Finish Family	No Finish
Amps	0.180-0.065A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lensed	Yes
Operating Position	Universal
Power Factor	>0.9
SDS Class	LED_Lamp
Product Technology	LED
Incandescent Equivalent	100W

### ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	25
Color Temp	Cool White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-25C (-13F) to +45C (+113F)
HID Equivalent	100W
Lumens	2000L
Volts	120V-277V
Watts	18W

### PHYSICAL

Lamp Base	Medium
Finish	Clear
Housing Color	WhiteGrey
ANSI Base	E26
Lamp Type	PAR38
MOD Lamps	4.75
MOL	5.0

### ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	No

### PACKAGING

UPC	045923097614
Case Cube	1.8958
Case Height	14.4
Case Length	18.2
Case Quantity	12
Case UPC	10045923097611
Case Weight	23.0
Case Width	12.5
EA Cube	0.1151
EA Height	6.1
EA Length	5.71
EA Quantity	1
EA Weight	0.99
EA Width	5.71
Inner Cube	1.252
Inner Height	6.89
Inner Length	17.72
Inner Quantity	6
Inner UPC	20045923097618
Inner Weight	11.5
Inner Width	17.72
Pack Type	Box
Web Length	5.0
Web Width	4.75

### COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24 Compliant	No
US State Ban	CA