



Project / Job Name:

Location:

Fixture Type:

Notes:

S9902 - 9 Watt T8 LED; 4000K; Medium Bi Pin base;
50000 Average rated hours; 1150 Lumens



GENERAL

Company	SATCO
EA Height	1.0
EA Width	1.0
EA Length	23.8
Lamp Ballast Type AB	Type A
Ballasting Requirements	May not be compatible with all rapid start ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required
Lamp Filament	LED
Fixture Type	Linear
Status	Obsolete
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.075-0.032A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Nominal Length	24.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	17W
Incandescent Equivalent	75W

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	210
Color Temp	Cool White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1150L
Volts	Ballast Dependent
Watts	9W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	Frost
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	24.0

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.

PACKAGING

UPC	045923099021
Case Cube	0.2669
Case Height	3.0
Case Length	24.4
Case Quantity	10
Case UPC	10045923099028
Case Weight	3.4
Case Width	6.3
EA Cube	0.0138
EA Height	1.0
EA Length	23.8
EA Quantity	1
EA Weight	0.28
EA Width	1.0
Pack Type	Sleeve
Web Length	24.0
Web Width	1.0

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No