



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9907 - 17 Watt T8 LED; 5000K; Medium Bi Pin base; 50000 Average rated hours; 2200 Lumens



GENERAL

| | |
|-------------------------|--|
| Company | SATCO |
| EA Height | 1.0 |
| EA Width | 1.0 |
| EA Length | 47.7 |
| Lamp Ballast Type AB | Type A |
| Ballasting Requirements | May not be compatible with all rapid start ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required |
| Lamp Filament | LED |
| Fixture Type | Linear |
| Status | Obsolete |
| CCT Selectable | No |
| Wattage Selectable | No |
| Finish Family | White |
| Amps | 0.142-0.061A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Frost |
| Lensed | Yes |
| Nominal Length | 48.0 |
| Operating Position | Universal |
| Power Factor | 0.9 |
| SDS Class | LED_Lamp |
| Product Technology | LED |
| Fluor Equiv | 32W |
| Incandescent Equivalent | 100W |

ELECTRICAL

| | |
|---------------------|-----------------------------|
| CCT (Kelvin Temp) | 5000K |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 210 |
| Color Temp | Natural Light |
| CRI | 80+ |
| Operating Frequency | 50/60Hz |
| Operating Temp | -4F to +113F (-20C to +45C) |
| Lumens | 2200L |
| Volts | Ballast Dependent |
| Watts | 17W |

PHYSICAL

| | |
|---------------|---------------|
| Lamp Base | Medium Bi Pin |
| Finish | Frost |
| Housing Color | White |
| ANSI Base | G13 |
| Lamp Type | T8 |
| MOD Lamps | 1.0 |
| MOL | 48.0 |

ADDITIONAL INFO

| | |
|--------------------|--------------------------------------|
| Warranty | 5-Years |
| Installation Notes | Not for use in vapor tight fixtures. |

PACKAGING

| | |
|---------------|----------------|
| UPC | 045923099076 |
| Case Cube | 0.5294 |
| Case Height | 3.0 |
| Case Length | 48.4 |
| Case Quantity | 10 |
| Case UPC | 10045923099073 |
| Case Weight | 6.1 |
| Case Width | 6.3 |
| EA Cube | 0.0276 |
| EA Height | 1.0 |
| EA Length | 47.7 |
| EA Quantity | 1 |
| EA Weight | 0.51 |
| EA Width | 1.0 |
| Pack Type | Sleeve |
| Web Length | 48.0 |
| Web Width | 1.0 |

COMPLIANCE

| | |
|-------------------|---------------------------------------|
| FCC Compliant | Yes |
| Location Rating | Damp |
| NSF Approved | Yes |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Certified, cULus - Classified |
| California Ban | Lawful for sale |
| DLC Approved | No |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |