



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S9919** - 43 Watt T8 LED; Single pin base; 5000K; 50000 Average rated hours; 5500 Lumens; Type B; Ballast Bypass; Double Ended Wiring



**GENERAL**

|                          |  |
|--------------------------|--|
| Company                  | SATCO  |
| EA Height                | 0.98   |
| EA Width                 | 0.98   |
| EA Length                | 93.78  |
| Lamp Ballast Type AB     | Type B   |
| Ballasting Requirements  | Ballast Bypass   |
| Lamp Filament            | LED  |
| Fixture Type             | Linear   |
| Status                   | Discontinued   |
| CCT Selectable           | No   |
| Wattage Selectable       | No   |
| Finish Family            | White  |
| Amps                     | 0.358-0.155A   |
| Has Camera               | No   |
| IOT Enabled              | No   |
| Lens Finish              | Gloss White  |
| Lensed                   | Yes  |
| Minimum Compartment Size | Length: 96.063 in. Width: 10.630 in. Height: 2.756 in. |
| Nominal Length           | 96.0   |
| Operating Position       | Universal  |
| Power Factor             | 0.9  |
| SDS Class                | LED_Lamp   |
| Shatter Proof Type       | Yes  |
| Product Technology       | LED  |
| Fluor Equiv              | 54W/59W  |
| Incandescent Equivalent  | 125W   |

**ELECTRICAL**

|                     |                             |
|---------------------|-----------------------------|
| CCT (Kelvin Temp)   | 5000K                       |
| Dimmable            | Non-Dimmable                |
| Hours Rated         | 50000                       |
| Beam Angle (degree) | 210                         |
| Color Temp          | Natural Light               |
| CRI                 | 80+                         |
| Operating Frequency | 50/60Hz                     |
| Operating Temp      | -4F to +113F (-20C to +45C) |
| Lumens              | 5500L                       |
| Volts               | 120V-277V                   |
| Watts               | 43W                         |

**PHYSICAL**

|           |             |
|-----------|-------------|
| Lamp Base | Single Pin  |
| Finish    | Gloss White |
| ANSI Base | Fa8         |
| Lamp Type | T8          |
| MOD Lamps | 1.0         |
| MOL       | 96.0        |

**ADDITIONAL INFO**

|                            |                                      |
|----------------------------|--------------------------------------|
| Warranty                   | 5-Years                              |
| Installation Notes         | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes                                  |

**PACKAGING**

|               |                |
|---------------|----------------|
| UPC           | 045923099199   |
| Case Cube     | 1.8417         |
| Case Height   | 4.33           |
| Case Length   | 95.7           |
| Case Quantity | 10             |
| Case UPC      | 10045923099196 |
| Case Weight   | 13.67          |
| Case Width    | 7.68           |
| EA Cube       | 0.0521         |
| EA Height     | 0.98           |
| EA Length     | 93.78          |
| EA Quantity   | 1              |
| EA Weight     | 0.26           |
| EA Width      | 0.98           |
| Pack Type     | Egg Crate      |
| Web Length    | 96.0           |
| Web Width     | 1.0            |

**COMPLIANCE**

|                 |                                       |
|-----------------|---------------------------------------|
| FCC Compliant   | Yes                                   |
| Location Rating | Damp                                  |
| NSF Approved    | Yes                                   |
| ROHS Compliant  | Yes                                   |
| Safety Listing  | cULus - Certified, cULus - Classified |
| California Ban  | Lawful for sale                       |
| DLC Approved    | No                                    |
| Title 20        | Exempt                                |
| T24 Compliant   | No                                    |