



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9929 - 12 Watt T8 LED; Medium bi-pin base; 5000K; 50000 Average rated hours; Type B Ballast Bypass; 1450 Lumens



GENERAL

Company	SATCO
EA Height	1.0
EA Width	1.0
EA Length	35.7
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Fixture Type	Linear
Status	Discontinued
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.100-0.043A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Nominal Length	36.0
Operating Position	Universal
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	25W
Incandescent Equivalent	60W

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	220
Color Temp	Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1450L
Volts	120V-277V
Watts	12W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	Frost
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	36.0

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.

PACKAGING

UPC	045923099298
Case Cube	0.3981
Case Height	3.0
Case Length	36.4
Case Quantity	10
Case UPC	10045923099295
Case Weight	4.6
Case Width	6.3
EA Cube	0.0207
EA Height	1.0
EA Length	35.7
EA Quantity	1
EA Weight	0.39
EA Width	1.0
Pack Type	Sleeve
Web Length	36.0
Web Width	1.0

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No