



**S9931** - 15 Watt T8 U-Bend LED; Medium bi-pin base; 3500K; 50000 Average rated hours; 1800 Lumens; Type B; Ballast Bypass; Single Ended Wiring


**GENERAL**

Company	SATCO
EA Height	1.4
EA Width	7.5
EA Length	23.2
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Fixture Type	U-Bend
Status	Obsolete
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.125-0.054A
Has Camera	No
IOT Enabled	No
Leg Spacing	6.0
Lens Finish	Frost
Lensed	Yes
Nominal Length	22.5
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	36W
Incandescent Equivalent	100W

**ELECTRICAL**

CCT (Kelvin Temp)	3500K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	220
Color Temp	Neutral White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	1800L
Volts	120V-277V
Watts	15W

**PHYSICAL**

Lamp Base	Medium Bi Pin
Finish	Frost
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	22.5

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

**PACKAGING**

UPC	045923099311
Case Cube	2.0847
Case Height	9.5
Case Length	24.0
Case Quantity	12
Case UPC	10045923099318
Case Weight	10.8
Case Width	15.8
EA Cube	0.141
EA Height	1.4
EA Length	23.2
EA Quantity	1
EA Weight	0.75
EA Width	7.5
Pack Type	Box
Web Length	22.5
Web Width	1.0

**COMPLIANCE**

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No