



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9942 - 43 Watt T8 LED; 6500K; Recessed Double Contact base; 50000 Average rated hours; 5500 Lumens; Type B; Ballast Bypass; Double Ended Wiring



GENERAL

Company	SATCO
EA Height	1.02
EA Width	1.02
EA Length	93.7
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Fixture Type	Linear
Status	Discontinued
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.358-0.155A
Has Camera	No
IOT Enabled	No
Lens Finish	Gloss White
Lensed	Yes
Minimum Compartment Size	Length: 96.063 in. Width: 10.630 in. Height: 2.756 in.
Nominal Length	96.0
Operating Position	Universal
SDS Class	LED_Lamp
Shatter Proof Type	Yes
Product Technology	LED
Fluor Equiv	110W
Incandescent Equivalent	125W

ELECTRICAL

CCT (Kelvin Temp)	6500K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	210
Color Temp	Daylight
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	5500L
Volts	120V-277V
Watts	43W

PHYSICAL

Lamp Base	Recessed Double Contact H0/VH0
Finish	Gloss White
ANSI Base	R17d
Lamp Type	T8
MOD Lamps	1.0
MOL	96.0

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures. Double ended wiring
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923099427
Case Cube	1.9547
Case Height	4.72
Case Length	95.67
Case Quantity	10
Case UPC	10045923099424
Case Weight	13.23
Case Width	7.48
EA Cube	0.0564
EA Height	1.02
EA Length	93.7
EA Quantity	1
EA Weight	0.97
EA Width	1.02
Pack Type	Egg Crate
Web Length	96.0
Web Width	1.0

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No