



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9950 - 23 Watt PLL LED ballast bypass; 2G11 base; 2800 Lumens; 120-277 Volt; 3500K; Type B; Ballast Bypass



GENERAL

Company	SATCO
EA Height	1.1
EA Width	1.8
EA Length	23.0
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Aluminum / Plastic
Fixture Type	PL
Status	Active
Style	Utility
Total Harmonic Distortion	20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	CCT Selectable Option: S18423
Amps	0.192-0.083A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	40W
Incandescent Equivalent	100W

ELECTRICAL

CCT (Kelvin Temp)	3500K
Hours Rated	50000
Beam Angle (degree)	270
Color Temp	Neutral White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	2800L
Volts	120V-277V
Watts	23W

PHYSICAL

Lamp Base	2G11 (4-Pin)
Finish	Frost
Housing Color	White
ANSI Base	2G11
Lamp Type	T5
MOD Lamps	0.63
MOL	22.5

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923099502
Case Cube	0.3935
Case Height	6.7
Case Length	23.6
Case Quantity	10
Case UPC	10045923099509
Case Weight	5.1
Case Width	4.3
EA Cube	0.0264
EA Height	1.1
EA Length	23.0
EA Quantity	1
EA Weight	0.45
EA Width	1.8
Pack Type	Box
Web Length	22.5
Web Width	0.63

COMPLIANCE

DLC ID	P007T912
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No