



## LED T8 Dimmable Ballast Compatibility Chart

Brand*	Model No.	Start Method	Number Of Lamps	Ballast Factor		Lamp Connection	1-Lamp	2-Lamp	3-Lamp	4-Lamp
				Type	Value					
General Electric	GE432MVPS-N-V03	DPS	4	N	0.90	Parallel	26.2%	17.4%	12.5%	10.0%
General Electric	GE232MVPS-L-S30	DPS	2	N	0.96	Parallel	23.8%	13.9%		
General Electric	GE132MVPSN-V03	DPS	1	N	0.88		13.0%			
General Electric	GE332MVPSN-V03	DPS	3	N	0.98	Parallel	22.4%	16.2%	18.3%	
Osram Sylvania	QHE 2X32T8/UNV DIM-TC	PRS	2	N	0.88	Series		4.0%		
Osram Sylvania	QTP2x32T8/UNV DIM-TC	DPS	2	N	0.88			3.3%		
Philips-Advance	IZT-2S32-SC	DPS	2	N	1.00	Series		4%~22%		
Philips-Advance	IZT-2PSP32-SC	DPS	2	N	1.00	Parallel	23.7%	6.0%		
Sunpark	U-232PS3	RS	2	N	0.88		33.5%	33.3%		
Sunpark	U-232PS3-HBF	RS	2	H	1.15		31.9%	30.3%		
Universal	B232PU104S50A	PRS	2	H	1.04	Parallel	25.8%	25.8%		

Applies to the following Satco products:

**S9938, S9939, S9940, S9941 11.5W 4ft. T8 - G4**

**Ballast Factors:**

L - Low  
N - Normal  
H - High

This list is current as of Feb. 2017. We are continuously testing for compatible ballasts. Please check back for updates.

\* All trademarks are the property of their respective owners

Copyright© 2017	Distribution Centers:	National Toll-Free:	110 Heartland Blvd.
Satco Products, Inc.	New York, Florida,	800-43-SATCO	Brentwood, NY 11717
All Rights Reserved.	Texas, Washington,	(800-437-2826)	PH 631-243-2022
Rev: February, 28 2017	California, Puerto Rico	<b>www.satco.com</b>	FX 631-243-2027